

ROCKBOND DUROMASTIC AR SEALER

Clear penetrating acrylic concrete sealer

DESCRIPTION

ROCKBOND Duromastic AR is a clear penetrating solvent acrylic solution with excellent durability against moisture and soiling. It is ideal for exposed aggregate and decorative concrete. It prevents the growth of mosses in wet weather and imparts an attractive permanent wet look.

SPECIAL PROPERTIES

- Fast drying (1 hour)
- Single pack
- No mixing required
- Stops dusting of floors
- Water repellent

USES

- Concrete floors
- Concrete curing agent
- Water repellent surface for brick and block work
- Primer sealer for Duromastic AC
- Reglaze for concrete tile roofs
- Sandstone

MIXING INSTRUCTIONS

As ROCKBOND DUROMASTIC AR SEALER (RB 7.10.03) is a ready-to-use product, no mixing whatsoever is required.

APPLICATION PROCEDURE

All surfaces to be clean, sound, free of oil and curing compounds and not more than slightly damp. Very dense concrete may need etching with ROCKBOND HYDROCHLORIC ACID (R.B.10.10)

WEATHERED OR AGED CONCRETE

Water-blast or acid etch and rinse. When dry, apply one or two coats of ROCKBOND DUROMASTIC AR SEALER (10.10) at 6-10m²/litre depending on porosity of concrete.

SANDSTONE

Must be free of dust and dry. Apply two or three coats at 6-8m²/litre. Apply with brush, roller or low pressure spray, taking care to achieve an even film without excess in low areas.

BRICK AND BLOCKWORK

Must be free of dust, moss and contaminants. When dry apply two coats of ROCKBOND DUROMASTIC AR SEALER (10.10) at 8-10m²/litre depending on porosity.

N.B. A permanent wet look will be achieved.

As this product has a wide and varied range of uses, we strongly recommend carrying out a small trial area to ensure suitability. Duromastic AR is not recommended as a hardwearing decorative floor glaze. Enquire about our Epotread AP Glaze in this application.

PACKAGING AND SIZE

20 Litre Plastic Containers and 200 Litre Metal Drums.

HEALTH AND SAFETY

Gives off highly flammable vapour. Keep well away from heat, sparks and open flame. Do not breath vapour or spray mist. Wear breathing respirator and ensure area is well ventilated. Avoid contact with skin and eyes. Wear eye protection and gloves. Do not drink.

TECHNICAL DATA

DRYING TIME	One hour approximately
RECOAT TIME	Three hours
LIGHT TRAFFIC	12-24 hours
WEATHER RESISTANCE	Good
COLOUR	Clear
SERVICE LIFE	Seven to ten years externally
TOXICITY	Non toxic after curing
APPLICATION TEMPERATURE	5°C - 30°C
SHELF LIFE	Indefinite if well sealed
CLEAN UP	Duromastic AR Thinners

TECHNICAL INFORMATION

Should you have any queries, or require further information, please contact our Technical Sales Team:

CONTACT DETAILS

T +64 4 568 5401 | F +64 4 568 4580



Rockbond SCP Ltd provides the above information in good faith and without warranty. The data represents typical values which can be updated at any time, and this information supersedes previous issues. No liabilities can be accepted for any damage or loss arising from the use of Rockbond SCP Ltd literature or its products, because Rockbond SCP Ltd has no continuous control on how the materials are mixed, placed or cured.

Revised January 2018