

ROCKBOND STEEL MOULD PROTECTOR - HG

Heavy Grade: Anti-Corrosion treatment

DESCRIPTION

ROCKBOND STEEL MOULD PROTECTOR – HG (10.41) is a natural lanolin based corrosion inhibitor designed to protect the steel moulds and casting beds used in the concrete precasting industry from rusting and pitting during storage. Outperforming many petroleum based products it forms a waxy film that preserves the surface of the mould, dramatically reducing the need to spend time and money getting mould back into a usable condition following storage

SPECIAL PROPERTIES

- Stops corrosion by preventing air and moisture attack.
- Shiny finish with minimal tackiness – Doesn't attract dust.
- Easy to use – No mixing required.
- Penetrates into surface rust, joints and grooves.
- Won't break down rubber components.
- Safe to use, Non Carcinogenic
- Environmentally friendly and biodegradable.
- Heavy grade – For 6 to 12 months protection and in for use in coastal areas

USES

- To protect steel concrete beam moulds during storage.
- To protect concrete casting beds when not in use.
- Any other rust prevention application
- As a general lubricant and penetrant

PACKAGING AND SIZE

ROCKBOND STEEL MOULD PROTECTOR – HG (10.41) is available in 5 litre, 20 Litre and 200 litre non-refundable containers

APPLICATION PROCEDURE

Shake container well and apply with a knapsack sprayer or compressed air system liberally coating the mould inside and out with ROCKBOND STEEL MOULD PROTECTOR – HG (10.41). Once completed place mould in storage. Additional touch ups may be required after long periods in storage.

REMOVAL

Removal is be steam cleaner or by using an approved degrease and water blasting. Contact Rockbond for information on appropriate degreasers.

IMPORTANT NOTES

If moulds need less than 6 months protection and aren't in coastal areas uses - ROCKBOND STEEL MOULD PROTECTOR – MG (10.40) this is easier to remove.

This product is not classified as a dangerous goods but is flammable. Keep away from naked flames.

HEALTH AND SAFETY

Rockbond Special Concrete Products are generally quite harmless, provided normal precautions are taken when handling chemicals.

Avoid contact with food stuffs and utensils. Avoid prolonged skin contact. Wear protective clothing, gloves, goggles etc. In the event of contamination wash thoroughly with water. If the eyes or mouth are affected wash with clean water and obtain medical attention.

TECHNICAL DATA

COLOUR:	Light Brown colour
SPECIFIC GRAVITY:	0.81 – 0.83kg/Litre
FLASH POINT:	66°C
VISCOSCITY:	(B-Viscos): 28.3
TOXICITY:	Non Toxic
DG CLASSIFICATION:	Non Hazardous
SHELF LIFE:	Unlimited in unopened original containers – But Shake Well before use
COVERAGE RATE:	Steel : 8 – 10m ² /Litre

TECHNICAL INFORMATION

Should you have any queries, or require further information, please contact our Technical Sales Team:

CONTACT DETAILS

T +64 4 568 5401 | F +64 4 568 4580



Rockbond SCP Ltd provides the above information in good faith and without warranty. The data represents typical values which can be updated at any time, and this information supersedes previous issues. No liabilities can be accepted for any damage or loss arising from the use of Rockbond SCP Ltd literature or its products, because Rockbond SCP Ltd has no continuous control on how the materials are mixed, placed or cured.

Revised January 2018