

ROCKBOND EVAPORATION RETARDER

Water based compound for control of shrinkage cracking

DESCRIPTION

ROCKBOND EVAPORATION RETARDER (RB 7.27) is a Surface-Active Agent in water solution, used to reduce the water evaporation rate from the surface of freshly laid flat concrete. When spray applied in diluted form to the surface of freshly laid plastic concrete it greatly reduced the tendency for surface plastic cracking (shrinkage cracking in plastic concrete) to occur during adverse weather conditions. Packaging is in 20 and 200 litre non-refundable container and has a shelf life of 2 years.

SPECIAL PROPERTIES

- Reduces the tendency for surface plastic cracking in freshly laid concrete.
- Trowelling aid that improves workability and finishing characteristics of cement surface.
- Extends surface workability time for any given set of weather conditions.
- Obviates the need for surface water sprays of fogging to maintain workability.
- Contains fugitive dye that shows area treated but will not stain the concrete in any way.

MIXING INSTRUCTIONS

ROCKBOND EVAPORATION RETARDER (RB 7.27) before use is to be diluted 1: 4 with water. Shake well after the addition of water.

APPLICATION PROCEDURE

Use spray equipment to apply a fine mist to completely cover the concrete surface with the diluted product. On very dry or windy days the preferred method of application is a backpack sprayer with a long wand. Application is most effective the sooner it is applied, preferably immediately after initial screeding. After spraying the surface, finish with normal floating. When working in hot dry conditions, a further application should be made after each finishing operation that is after wood floating, steel trowelling etc.

ROCKBOND EVAPORATION RETARDER (RB 7.27) is not a curing agent, and application of ROCKBOND SLABCURE (RB 7.10) or ROCKBOND MEMBRANE CURE (RB 7.11) should proceed as soon as trowelling of surface is complete.

Not suitable for application onto vertical surface or where excessive run-off of the diluted solution may occur.

COVERAGE

ROCKBOND EVAPORATION RETARDER (RB 7.27) diluted 1: 4 with water will cover 10 sq metres per litre when spray applied to a flat concrete surface that has had an initial screeding.

HEALTH AND SAFETY

ROCKBOND EVAPORATION RETARDER (RB 7.27) is non-toxic and safe to use. However, if splashes enter the eyes, product must be washed out immediately with plenty of clean running water. Continue the treatment for several minutes with the eyelids kept open. If the product is ingested, give the patient plenty of water to

drink. Wear goggles, a mask and protective clothing while handling, spraying and applying the material. The product is slippery when spilt.

IMPORTANT NOTE

When stored, ROCKBOND EVAPORATION RETARDER (RB 7.27) should be protected from frost, direct sunlight and away from localised heat sources. Keep containers closed when not in use.

TECHNICAL DATA

COLOUR	Dark green liquid
SPECIFIC GRAVITY	1.03 Kg/Litre
pH	6.0 – 8.0

TECHNICAL INFORMATION

Should you have any queries, or require further information, please contact our Technical Sales Team:

CONTACT DETAILS

T +64 4 568 5401 | F +64 4 568 4580



Rockbond SCP Ltd provides the above information in good faith and without warranty. The data represents typical values which can be updated at any time, and this information supersedes previous issues. No liabilities can be accepted for any damage or loss arising from the use of Rockbond SCP Ltd literature or its products, because Rockbond SCP Ltd has no continuous control on how the materials are mixed, placed or cured.