

TECHNICAL DATA SHEET

ARMORTECH AT32

Release Agent and Protector for Asphalt Assets

DESCRIPTION

Rockbond ArmorTech AT32 is a ready-to-use, liquid asphalt release agent, that is odourless and free from harmful solvents.

Designed for the protection and maintenance of asphalt plants, transport vehicles, and related machinery, ArmorTech AT32 reflects Rockbond's commitment to high-quality performance and environmental sustainability.





PRODUCT DETAILS

- Free from hazard symbol
- Rainproof
- Solvent-free
- Corrosion resistant
- Lubricating effect

PHYSICAL PROPERTIES

- | | |
|------------------------|--------------------------------|
| • Colour | Pale yellow to gold Slight |
| • Odour | Musky |
| • Density | 920kg/m ³ @ 15°C |
| • Flash point | > 325 °C |
| • Viscosity, kinematic | 78.2 mm ² /s @ 20°C |

CONSUMPTION

40 m²/l

STORAGE

- | | |
|--------------------------|--|
| • Packaging materials | Only store product in original container |
| • Storage temperature | 0 – 35 °C |
| • Maximum storage period | 24 months |

Limited shelf life after opening. External factors such as (high) temperature, direct sunlight and frost can have a negative influence on the shelf life of the product. Use container to collect drips

PRODUCT/PACKAGING DISPOSAL RECOMMENDATION

Dispose in a safe manner in accordance with local/national regulations, Remove to an authorized waste treatment plant.

APPLICATION

Flatbeds of asphalt trucks and asphalt tools

PROCESSING

The product is ready to use and must not be mixed with other products.

We recommend a low-pressure stainless steel hand sprayer for applying the products. We advise you to contact our advisors the correct nozzle.

Product can be used immediately after application.

PACKAGING

Can (20 litres)
Drum (210 liters)
Container (1000 litres)

TECHNICAL INFORMATION

Should you have any queries, or require further information, please contact our **Technical Sales Team: +64 4 568 5401**